

Specification of Battery Charger

ES120W

29.4V2A

29.4V / 2A Li-ION / BATTERY CHARGER



General

ES120W 135×90×50mm 29.4vdc/2A

Battery Charger **ES120W 135×90×50mm** can work normally under **29.4vdc/2A** and with reverse polarity protection.

Main product specification

Max.output power	Input voltage	Output voltage	Combined regulation	Output current	Combined regulation
120W	220V	29.4V+/-0.2V DC	+/-0.2V	2A	+/-0.2A

Environmental condition

No.	Item	Technical specification	Remark
1	Humidity	5~95%	With package
2	Altitude	≤5000m	Work normally

Electrical characteristics

4.1

Input characteristic

No.	Item	Technical specification	Remark
1	Rated input voltage	220Va	
2	Input voltage range	180~ 240Vac	
5	AC input voltage frequency	50~60 Hz	

4.2

Output characteristic or charge stages

No.	Item	Technical specification	Remark
1	CC(constant current)	≤29.4vdc, 2A	
2	CV(constant voltage)	29.4vdc, 2A ↓	
4	Power efficiency	≥90%	=250Vac, Vin=250Vac, rated load

4.5

Protection characteristics

No.	Item	Technical specification	Remark
1	Over voltage protection	Yes	
2	Software over voltage protection	The charger software limits the maximum output voltage to a level suitable for the connected battery system.	
5	Thermal protection	No	
4	Current limiting protection	Yes	At CC mode
5	Short circuit protection	Short circuit protection should be automatically recovery after remove the condition.	
6	Reverse polarity protection	When output wires are reversely connected to the battery the charger will not operate and will work normally when DC wires are correctly connected.	

4.4

Charging indicator

No.	Item	Status	Remark
1	Power on	LED1: Red	
2	Charging	LED2: Red	
5	Fully charged	LED2: Green	
4	Charging Voltage Display	YES	
5	Charging Current Display	YES	

Safety & EMC

No.	Item		Standard (or test condition)	Remark
1	Electric strength test	Input-output	1500Vac/10mA/1min	No breakdown
2	Isolation resistance	Input-ground	$\geq 10\text{Mohm}@500\text{Vdc}$	
		Output-ground	$\geq 10\text{Mohm}@500\text{Vdc}$	
5	Leakage current		$< 5.5\text{mA}$	Vin=264Vac
4	LVD		EN60555-1:2002+EN60555-2-29:2002	

Remark: Discrimination A- Function OK under technical requirement range;

Discrimination R- Physical damage or failure of equipment are not allowed, but damage of protection device (fuse) caused by interference signal of outside is allowed, and the whole equipment can work normally after replacement of protection device and reset of running parameter

Environmental testing requirements

No.	Item	Technical specification	Remark
1	High temperature ambient operating	+40°C	Features OK
2	Low temperature ambient operating	-10°C	Features OK
5	High temperature storage	+70°C	Work normally after recovery under normal temperature for 2 hours
4	Low temperature storage	-40°C	Work normally after recovery under normal temperature for 2 hours
5	Random vibration	20Hz to 2000Hz 5Grms 20hours per axis	
6	Repetitive shock	40g peak 5 orthogonal axes, 5+ and 5- in each axis, 11ms pulse width	
7	Thermal shock	-55°C to 75°C, <5min transition, 2.5hours dwell, 200cycle	
8	Drop test	BS EN60068-2-52:1995 TEST ED: free fall appendix B	

Mechanical characteristic:

Shell material: Aluminum

Outline dimension: L*W*H=135×90×50mm

Input socket: meets IEC standard

AC wires: 1.5m length

DC wire: 0.85m length

Net Weight: 0.8Kg

8. Package, transportation & storage

8.1 Package:

There is product name, model, name of manufacturer, safety approval, serial number, User Manual and packing list in the package box.

8.2 Transportation:

Suit for transportation by truck, the products should be shielded by tent from sunshine, and loaded and unloaded carefully.

8.5 Storage:

Products should be stored in package box when it is not used. And warehouse temperature should be $-40\sim 70^{\circ}\text{C}$, and relative humidity is 5~95%. In the warehouse, there should not be harmful gas, inflammable, explosive products, and corrosive chemical products, and strong mechanical vibration, shock and strong magnetic field affection. The package box should be above ground at least 20cm height, and 50cm away from wall, thermal source, and vent. Under this requirement, product has 2 years of storage period, and should be rechecked when over 2 years.

9. Reliability requirements

MTBF $\geq 50\text{K}$

MTBF (standard, environmental temperature, load requirement) $\geq 50\text{K}$ hours;

testing condition: 25°C , full load, testing proved value.

10.

Charging Curve

