

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C. (518101)

Material Safety Data Sheet (MSDS)

KEEPPOWER TECHNOLOGY CO., LIMITED

5F, Bldg 4, Fenmenao Industrial Park, Bantian, Long Gang, Shenzhen 518129, China and for their product

Protected 16340 800mAh Battery

Model/type reference RCR123A

Trademark KEEPPOWER

Nominal Voltage..... 3.7V

Typical Capacity...... 800mAh, 2.96Wh

17.9g Weight....:

H: 34.3mm Shape and Physical Dimension (mm).....: D: 16.4mm

Version number..... V5.0

Preparation Date...... Apr. 03, 2020

Revision date...... N/A.

Laboratory Shenzhen SEM Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Address:

Road, Bao'an District, Shenzhen, P.R.C. (518101)

Compiled by (name+ signature)

Approved by (name+ signature) ...







1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C. (518101)

Material Safety Data Sheet

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Identifier

Product name: Protected 16340 800mAh Battery

Model: RCR123A

Other means of identification

Synonyms:none

Recommended use of the chemical and restrictions on use

Recommended Use: Used in portable electronic equipments;

Uses advised against:

- a) Do not dismantle, open or shred secondary cells or batteries.
- b) Do not expose cells or batteries to heat or fire. Avoid storage in direct sunlight.
- c) Do not short-circuit a cell or a battery. Do not store cells or batteries haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects.
- d) Do not remove a cell or battery from its original packaging until required for use.
- e) Do not subject cells or batteries to mechanical shock.
- f) In the event of a cell leaking, do not allow the liquid to come in contact with the skin or eyes. If contact has been made, wash the affected area with copious amounts of water and seek medical advice.
- g) Do not use any charger other than that specifically provided for use with the equipment.
- h) Observe the plus (+) and minus (-) marks on the cell, battery and equipment and ensure correct use.
- i) Do not use any cell or battery which is not designed for use with the equipment.
- j) Do not mix cells of different manufacturer, capacity, size or type within a device.
- k) Battery usage by children should be supervised.
- I) Seek medical advice immediately if a cell or a battery has been swallowed.
- m) Always purchase the battery recommended by the device manufacturer for the equipment.
- n) Keep cells and batteries clean and dry.
- o) Wipe the cell or battery terminals with a clean dry cloth if they become dirty.
- p) Secondary cells and batteries need to be charged before use. Always use the correct charger and refer to the manufacturer's instructions or equipment manual for proper charging instructions.
- q) Do not leave a battery on prolonged charge when not in use.
- r) After extended periods of storage, it may be necessary to charge and discharge the cells or batteries several times to obtain maximum performance.
- s) Retain the original product literature for future reference.
- t) Use only the cell or battery in the application for which it was intended.
- u) When possible, remove the battery from the equipment when not in use.
- v) Dispose of properly.

Details of the supplier of the safety data sheet:

Supplier Name: KEEPPOWER TECHNOLOGY CO., LIMITED

Address: 5F, Bldg 4, Fenmenao Industrial Park, Bantian, Long Gang, Shenzhen 518129, China

Telephone number of the supplier: 86 755 8995 6056 Emergency Telephone No.(24h): 86 755 8995 6056

Fax: 86 755 8930 9659

Report No.: WTX20X03010844B Page 2 of 10





1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C. (518101)

Material Safety Data Sheet

E-mail address: info@keeppower.com.cn

Emergency telephone number

Company Emergency Phone Number: 86 755 8995 6056

2. HAZARDS IDENTIFICATION

Classification: (see section 14)

No harm at the normal use. If contact the Electrolyte liquid in the Protected 16340 800mAh Battery, reference as follows:

Classification of the substance or mixture

Classification according to GHS

Acute Toxicity, Oral(Hazard category 4)

Acute Toxicity, Dermal(Hazard category 3)

Skin, irritate(Cagegory 1B)

Eye Irritate (Hazard category 1)

GHS Label elements, including precautionary statements:



GHS02



GHS05



GHS06

Signal word: Warning Hazard statement(s):

H242:Heating may cause a fire; **H311:** Toxic in contact with skin;

H314: Causes severe skin burns and eye damage;

H302:Harmful if swallowed; precautionary statements:

Prevention:

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P312:Call a Poison center or doctor/physician if you feel unwell.

P302+P350-IF ON SKIN: Gently wash with plenty of soap and water

P301+P330+P331-IF SWALLOWED: rise mouth. Do NOT induce vomiting

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage:

None

Disposal

P501: Dispose of contents/container in accordance with local/national regulations

Hazards not otherwise classified (HNOC)

Not Applicable

Other information

Report No.: WTX20X03010844B Page 3 of 10



1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C. (518101)

Material Safety Data Sheet

No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical characterization: Mixtures

Description:

Product: Consisting of the following components.

Common Chemical Name	Concentration (%)	CAS Number	EC No.
Cobalt lithium manganese nickel oxide	30-45	182442-95-1	
Graphite Powderr	15-25	7782-42-5	231-955-3
Lithium hexaflurorphosphate (LiPF6)	1-3	21324-40-3	244-334-7
Poly (vinylidene fluoride) (PVDF)	0.1-4	24937-79-9	
Aluminum foil	2-8	7429-90-5	231-072-3
Copper foil	5-10	7440-50-8	231-159-6
Carbon black and others	0.5-3	1333-86-4	215-609-9
Styrene, 1,3-butadiene polymer	0.5-5	9003-55-8	

Note: CAS number is Chemical Abstract Service Registry Number.

N/A=Not apply.

4. FIRST-AID MEASURES

First aid measures

Eye Contact Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.

Skin Contact Remove contaminated clothing and shoes. Wash skin with soap and water. In the case of skin irritation or allergic reactions see a physician.

Inhalation Move to fresh air. If symptoms persist, call a physician.

Ingestion Do NOT induce vomiting. Drink plenty of water. If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed

Swallowing Do not induce vomiting. Get medical attention.

Most Important Symptoms/Effects No information available.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

CO2, dry chemical powder, water spray.

Report No.: WTX20X03010844B Page 4 of 10





1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C. (518101)

Material Safety Data Sheet

Unsuitable Extinguishing Media: No information available.

Specific Hazards Arising from the Chemical

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide(CO)

Carbon dioxide

Other irritating and toxic gases.

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No

Sensitivity to Static Discharge No

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. For example: Wear self-contained respiratory protective device. Wear suitable protective clothing and eye/face protection.

Special hazards arising from the substance or mixture:

Battery may burst and release hazardus decomposition products when exposed to a fire situation. Lithium ion batteries contain flammable electrolyte that may vent, ignite and produce sparks when subjected to high temperature(>150°C), When damaged or abused(e.g. mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in clothes proximity.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid contact with eyes.

Refer to section 8 for personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

Evacuate personnel to safe areas.

Environmental precautions

Environmental Precautions Refer to protective measures listed in Sections 7 and 8.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning up Use personal protective equipment. Dam up. Cover liquid spill with sand, earth or other Non combustible absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Precautions for safe handling

Report No.: WTX20X03010844B Page 5 of 10





1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C. (518101)

Material Safety Data Sheet

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Wear personal protective equipment.

Wash thoroughly after handling. Use this material with adequate ventilation.

The product is not explosive.

Conditions for safe storage, including any incompatibilities

If the Protected 16340 800mAh Battery is subject to storage for such a long term as more than 3 months, it is recommended to recharge the Protected 16340 800mAh Battery periodically. 3 months: -10 $^{\circ}$ C~+40 $^{\circ}$ C, 45 to 85%RH

And recommended at 0°C~+35°C for long period storage.

The capacity recovery rate in the delivery state (50% capacity of fully charged) after storage is assumed to be 80% or more.

The voltage for a long time storage shall be 3.0V~4.2V range.

Do not storage Protected 16340 800mAh Battery haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects.

Keep out of reach of children.

Do not expose Protected 16340 800mAh Battery to heat or fire. Avoid storage in direct sunlight.

Do not store together with oxidizing and acidic materials.

Keep ignition sources away- Do not smoke.

Store in cool, dry and well-ventilated place.

Incompatible Products None known.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Control parameters

Ingredients with limit values that require monitoring at the workplace:			
TLV (USA)	0.02mg/m ³		
MAK (Germany)	0.1mg/m ³		

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962(11th Cir., 1992).

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations

Ventilation systems

Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits. Ensure adequate ventilation.

Individual protection measures, such as personal protective equipment

Eye/Face Protection:



Tightly sealed goggles

Body protection:

Protective work clothing.

Skin protection:

Report No.: WTX20X03010844B Page 6 of 10



1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C. (518101)

Material Safety Data Sheet



Protective gloves

Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material:

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

	Form: Cylindrical			
Physical	Color: Black			
State	Odour: Odourless			
	Odor Threshold: No information available			
Change in condition:				
pH, with indication of the concentration		Not determined.		
Melting point/freezing point		Not determined.		
Initial boiling point and Boiling range:		Not determined.		
Flash Point		Not determined.		
Evaporation rate		Not determined.		
Flammability (solid, gas)		Not determined.		
Upper/lower flammability or explosive limits		Not determined.		
Vapor Pressure:		Not determined.		
Vapor Density:		Not determined.		
relative den	sity:	Not determined.		
Solubility in Water:		Not determined.		
Solubility in other solvents		Not determined.		
n-octanol/water partition coefficient		Not determined.		
Auto-ignition temperature		Product is not self-igniting.		

Report No.: WTX20X03010844B Page 7 of 10





1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C. (518101)

Material Safety Data Sheet

Decomposition temperature	Not determined.
Odout threshold	Not determined.
Evaporation rate	Not determined.
Viscosity	Not determined.
Other Information	No further relevant information available.

10. STABILITY AND REACTIVITY

<u>Reactivity:</u> Stable under recommended storage and handling conditions (see section 7, Handling and storage).

Chemical stability: Stable under normal conditions of use, storage and transport.

Thermal decomposition/conditions to be avoided: No decomposition if used according to specifications.

Possibility of Hazardous Reactions: None under normal processing.

Hazardous Polymerization: Hazardous polymerization does not occur.

Conditions to avoid: Strong heating, fire, Incompatible materials.

Incompatible materials: Strong oxidizing agents. Strong acids.Base metals.

<u>Hazardous Decomposition Products:</u>Carbon oxides, Other irritating and toxic gases.

11. TOXICOLOGICAL INFORMATION

Acute toxiciy: No data available.

LD/LC50 values relevant for classification:

Not available.

Skin corrosion/irritation: No irritant effect.

Serious eye damage/irritation: Cause serious eye irritation.

Respiratory or skin sensitization: No sensitizing effects known.

Specific target organ system toxicity: No information available.

CMR effects(carcinogenity, mutagenicity and toxicity for reproduction): No information

available.

12. Ecological Information

Toxicity:

Acquatic toxicity:

No further relevant information available.

Persistence and degradability: No further relevant information available.

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

Results of PBT and vPvB assessment

Report No.: WTX20X03010844B Page 8 of 10





1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C. (518101)

Material Safety Data Sheet

PBT: Not applicable. vPvB: Not applicable.

Other adverse effects: No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Recommendation: Must not be disposed together with household garbage.

Do not allow product to reach sewage system

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

14. TRANSPORT INFORMATION

The dangerous goods regulations require that each battery design be subject to tests contained in Section 38.3 of UN Manual of Tests and Critical prior to being offered for transportation.

The packaging shall be adequate to avoid mechanical damage during transport, handling and stacking. The materials and pack design shall be chosen so as to prevent the development of unintentional electrical conduction, corrosion of the terminals and ingress of moisture.

UN number : UN3480 or UN3481;

UN Proper shipping name/Description (technical name): Lithium ion batteries or Lithium ion batteries contained in equipment or Lithium ion batteries packed with equipment;

UN Classification (Transport hazard class): Class 9 dangerous goods;

When the following requirements are met, can be shipped without being declared as Class 9 dangerous goods:

- 1: Shipped by air meets the requirement of Packing Instructions PI965, PI966 and PI967 Section II appropriate of IATA Dangerous Goods Regulations 61st Edition(IATA DGR 61st) for transportation;
- 2: Shipped by sea meets the requirement of Special Provision 188 appropriate of International Maritime Dangerous Good Code (IMDG CODE 39-18) for transportation;
- 3: Shipped by road meets the requirement of Special Provision 188 appropriate of International Carriage of Dangerous Goods by Road (ADR 2019) for transportation;
- 4: Shipped by rail meets the requirement of Special Provision 188 appropriate of International Carriage of Dangerous Goods by Rail (RID 2019) for transportation;

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation:

Authorisations: No information available.

Report No.: WTX20X03010844B Page 9 of 10





1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C. (518101)

Material Safety Data Sheet

Restrictions on use: No information available.

Regulatory information

CAS No.	EU	US	Japan	Canada	Australia	Korea	China
	(EINECS)	(TSCA)	(ENCS)	(DSL/	(AICS)	(ECL)	(IECSC)
				NDSL)			
182442-95-1	Listed	Not listed	Not listed	NDSL	Not listed	Not listed	Not listed
7782-42-5	Listed	Listed	Listed	DSL	Listed	Listed	Listed
21324-40-3	Listed	Listed	Listed	DSL	Listed	Listed	Listed
24937-79-9	Not listed	Listed	Not listed	DSL	Listed	Listed	Listed
7429-90-5	Not listed	Listed	Not listed	DSL	Listed	Listed	Listed
7440-50-8	Listed	Listed	Listed	DSL	Listed	Listed	Listed
1333-86-4	Listed	Not listed	Not listed	Not listed	Not listed	Not listed	Listed
9003-55-8	Listed	Listed	Not listed	NDSL	Not listed	Not listed	Not listed

Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

Transportation regulations

IATA Dangerous Goods Regulations 61st Edition(IATA DGR 61st), effective January 1,2020 International Maritime Dangerous Good Code (IMDG CODE 39-18), effective January 1,2019 International Carriage of Dangerous Goods by Road (ADR 2019), effective January 1,2019 International Carriage of Dangerous Goods by Rail (RID 2019), effective January 1,2019

16. OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Reference:

ISO 11014:2009 Safety data sheet for chemical products-Content and order of sections GB/T 16483-2008 Safety data sheet for chemical products-Content and order of sections

Relevant phrases:

R20/22: Harmful by inhalation and if swallowed.

R36: Irritating to eyes.

H302: Harmful if swallowed. H332: Harmful if inhaled.

Report No.: WTX20X03010844B Page 10 of 10